

MULTI-FINISHER











Range of tensioning multi-finishers for shirts and outerwear, either laundered or dry-cleaned. These units are particularly recommended for dry-cleaning shops, hotels and nursing homes.

With the new "AF LOGIC" controls, the operator can switch from one mode to another by SIMPLY pressing a key, thus automatically setting the unit to operate according to the required parameters.

**404** new pneumatic trolley for fast and accurate alignment with the shirt hem, two air-operated side clamps which can pneumatically expand on cycle start, and one air-operated rear clamp. Pneumatic closing of the front paddle, with steam-heated vacuum counter-paddle for an easier dressing of shirts and outerwear. Manual collar locking system. Available with photocell on rear clamp and pneumatic rotating sleeve clamps, which are particularly recommended for finishing shirt

This shirt unit doesn't require trained personnel. A few hours of practice are enough to achieve excellent results and stunning performances, indeed.

## This unit features three operation modes:

• SHIRT, for shirts and lab-coats

• WET, for wet-cleaned outerwear

• DRY, for dry-cleaned outerwear.

## Included as standard:

• padded flexible paddles to prevent: shine marks on dark fabrics, paddle pressure marks, button marks on the shirt;

• two front interchangeable paddles;

• cycle-extension button; • manual cycles available;

• electric iron for touch-ups.

TECHNICAL DATA	404
POWER	220/3/60Hz
BLOWING MOTOR	1,5 kW
VACUUM MOTOR	0,25 Kw
STEAM INLET	1/2"
RETURN OUTLET	1/2"
STEAM WORKING PRESSURE	58 ÷ 87 psi
STEAM CONSUMPTION	55 ÷ 66 Lbs/h
COMPRESSED AIR INLET	1/4"
AIR WORKING PRESSURE	87 ÷ 116 psi
COMPRESSED AIR CONSUMPTION	3,1 cubic feet/cycle
MAX DIMENSION IN OPERATION	59 x 98,5 in
NET WEIGHT	666 Lbs
GROSS WEIGHT PALLET + SPECIAL EXPORT CARTON	705 Lbs
PACKAGE DIMENSIONS	64 x 32 x 81 in
VOLUME	63 ft3

