

FORMPLUS/S









• pinze pneumatiche laterali e posteriore

FORMPLUS/S tensioning form finisher has been designed to fulfil demands of a Wet Cleaning pressing system that requires vertical tensioning for perfect seam finishing and fabric "revitalising". Suitable for jackets, coats, raincoats, lumber jackets, leather garments, dresses and also many other speciality applications of any fabric and size. It features a special tensioning system for the garment being processed and the powerful hot air flow provides a high class finish. Automatic positioning of the dummy is accomplished using a photocell. A powerful and flexible microprocessor allows cycles to be programmed and saved. It is supplied ready for connection to an external steam supply.

Using the FORMPLUS for dry cleaned garments, a very high standard of finish will be achieved. Any final touching-up (if at all) is restricted to very minor details. Using the FORMPLUS, you will see improved hourly output and significantly, no specialised labour is required to produce excellent results.

Included as standard:

- microprocessor allowing up to 10 programs to be customised saved;
- 270° rotating dummy;
- lateral and rear pneumatic clamps for vents;
- GFV steam iron assembly complete with ALL STEAM iron for final touch-up.

TECHNICAL DATA	FORMPLUS/S
REQUIRED POWER	220 V/3/60 Hz
FAN MOTOR	1,1 kW
STEAM INLET	1/2"
RETURN OUTLET	1/2"
STEAM WORKING PRESSURE	70 ÷ 87 psi
STEAM CONSUMPTION	33 ÷ 44 Lbs/h
AIR INLET	1/4"
AIR WORKING PRESSURE	87 ÷ 100 psi
AIR CONSUMPTION	0,35 cubic feet/cycle
ENCUMBRANCE	41x50x93 max ÷ 63min in
NET WEIGHT	297 Lbs
GROSS WEIGHT	364 Lbs
PACKAGE DIMENSIONS	38 x 35 x 70 in
VOMUNE	53 Ft3

