DRY CLEANING PRESSES

ETL
LISTED
c us

PONY
USA
FINISHING FIRST

PONY
PRESSING AND FINISHING MACHINERY

Finishing presses for the laundry, drycleaning and manufacturing industries.

Wide range of professional finishing presses with a compact design, combining power, functionality and rapidity. Four different lines are produced to allow a rational and diversified choice, able to meet all requirements. Presses are available with different shaped heads and bucks both padded (steaming head and steam/vacuum buck; also blowing by request) or with nickel-plated polished head (steaming and vacuum buck). All presses are ready for connection to external steam and vacuum supplies.

CPS-Colox press special

Air operated presses with one plus one button head closing complete with head safety guard.
Highly professional, with very fast head movement and extra strong adjustable squeezing pressure.

....

Features:
- a balanced head using special self adjusting springs allowing optimal alignment of head and buck;
- the head opens to an angle of 60° - Copious and instant live steam production thanks to pneumatic valves for steam distribution to both the head and buck - Easy access to the controls with an adjustable pedal for the maximum comfort of the operator (CPS-U and CP-UP).

....

Included as standard:
UP
- automatic system of the finishing cycle;
- steam iron assembly.

U
- steam iron assembly.

TECHNICAL DATA	CP-U SPECIAL UTILITY SHAPE	CP-UP SPECIAL UTILITY LEGGER SHAPE
REQUIRED POWER	110V/1/60 Hz	110V/1/60 Hz
VACUUM EXHAUST	Ø4 in	Ø4 in
STEAM INLET	1/2"	1/2"
CONDENSATION RETURN	1/2"	1/2"
STEAM WORKING PRESSURE	79,7 psi	79,7 psi
STEAM CONSUMPTION	30,8 ÷ 55,1 Lbs/h	30,8 ÷ 55,1 Lbs/h
COMPRESSED AIR INLET	3/8"	3/8"
AIR WORKING PRESSURE	100 psi	100 psi
COMPRESSED AIR CONSUMPTION	4,9 cubic feet/cycle	4,9 cubic feet/cycle
DIMENSIONS	49 x 45 in	49 x 45 in
NET WEIGHT	622 Lbs	633 Lbs
GROSS WEIGHT PALLET + SPECIAL EXPORT CARTON	661 Lbs	672 Lbs
PACKAGE DIMENSIONS	54 x 45 x 57 in	54 x 45 x 57 in
VOLUME	79,8 ft3	79,8 ft3

CP-U SPECIAL UTILITY SHAPE

CP-UP SPECIAL UTILITY LEGGER SHAPE

AVAILABLE SHAPES

CP-U Special
R=700
R=28"
1190
47"
360
15"
220
9"

CP-UP Special
R=650
R=650
R=25,5"
1190
47"
470
18,5"
205
8"