

MG
UNIVERSAL
FORM
FINISHERS



PONY USA
FINISHING FIRST

MG form finisher for connection to external steam supply that meets the demand for a blow finish for all outerwears (jackets, coats, etc.) in dry cleaning and laundry stores, the garment industry, ironing services and in the hospitality industry. This form finisher boasts an aesthetic design and high quality overall finishing. Available with standard dummy.

OTHER FEATURES:

- finishing cycles controlled by microprocessor with 10 stored programs;
- manual cycle start or automatic cycle start using a foot pedal;
- adjustable hot air flow;
- revolving dummy;
- all parts in contact with steam are made of stainless steel.



MG

UNIVERSAL FORM FINISHER

Technical data (standard equipment)	
EN	STEAM-FED
Required power	110V/1/60Hz
Fan motor	1,50 HP
Power assorbed	1,50 HP
Current assorbed	9,50 A
Steam inlet	1/2 "
Condensation return	1/2 "
Steam working pressure	58,00 ÷ 87,00 psi
Steam consumption	22,00 ÷ 33,00 lb/h
Dimensions	23,00 x 46,00 in
Net weight	176,00 lb
Gross weight pallet+special export carton	220,00 lb
Package dimensions	56,00 x 31,00 x 43,00 in